

# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Foreign Crude Oil

## SECTION 1: IDENTIFICATION

### Product identifier

Product name Foreign Crude Oil  
CAS No 8002-05-9

### Other means of identification

Crude Oil Peregrino, Castilla Crude Oil, Escalante Crude Oil, Vasconia Crude Oil, Petróleo Crudo.

### Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Raw material for petroleum refining products.  
Uses advised against Anything other than the above.

### Details of the supplier of the safety data sheet

Supplier Vitol Inc.  
2925 Richmond Ave, 11th Floor  
Houston, TX 77098  
Telephone (713) 230-1000  
Fax 713-230-1185  
E-mail (competent person) SDSHOU@vitol.com

### Emergency telephone number

Emergency Phone No. Chemtrec: US/Canada: 1-800-424-9300 (24h)  
Mexico: 800 681 9531 (24h)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards Flammable Liquid, Category 1  
Health hazards Aspiration hazard, Category 1  
Eye Irritation, Category 2A  
Specific target organ toxicity — single exposure, Category 3 (Narcotic effects)  
Carcinogen, Category 1B  
Specific target organ toxicity — repeated exposure, Category 2  
Environmental hazards Hazardous to the aquatic environment, Chronic, Category 2

### Label elements

Hazard Pictogram(s)



Signal Word(s)

DANGER

Hazard Statement(s)

Extremely flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes eye irritation.  
May cause drowsiness or dizziness.  
May cause cancer.  
May cause damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life with long lasting effects.

Precautionary Statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.

# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Foreign Crude Oil

Store in a well-ventilated place. Keep cool.  
Obtain special instructions before use.  
Do not breathe vapour.  
Wear protective gloves/eye protection/face protection.  
IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
Immediately call a POISON CENTER/doctor.  
Do NOT induce vomiting.  
Avoid release to environment.  
Dispose of contents in accordance with local, state or national legislation.

## Other hazards

The vapour is heavier than air; beware of pits and confined spaces. May cause irritation to eyes and air passages. Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

## Percent of the mixture consists of ingredient(s) of unknown acute toxicity:

0% of the mixture consists of ingredients of unknown acute inhaled toxicity.  
0% of the mixture consists of ingredients of unknown acute oral toxicity.  
0% of the mixture consists of ingredients of unknown acute dermal toxicity.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Substances

Classification: OSHA HCS (29 CFR 1910.1200)

Chemical identity of the substance	%W/W	CAS No.	EC No.
Petroleum	100	8002-05-9	232-298-5

### Hazardous constituents

Chemical identity of the substance	%W/W	CAS No.	EC No.
N-hexane	0 - 5	110-54-3	203-777-6
Sulfur	0 - 2	7704-34-9	231-722-6
Hydrogen Sulfide	-	7783-06-4	231-977-3
Benzene	-	71-43-2	200-753-7
Toluene	-	108-88-3	203-625-9

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Self-protection of the first aider

Avoid all contact. Do not breathe vapour. Eliminate sources of ignition. If it is suspected that fumes are still present, the responder should wear an appropriate mask or self-contained breathing apparatus. Drench contaminated clothing with water before removing to avoid risk of sparks from static electricity. Do not use mouth-to-mouth resuscitation. No action should be taken involving personal risk. Wear appropriate personal protective equipment, avoid direct contact. Do not ingest. If swallowed then seek immediate medical assistance.

H2S Warning:

Hydrogen sulphide (H2S) can accumulate in the headspace of storage tanks and reach potentially hazardous concentrations.

Inhalation

If there is any suspicion of inhalation: A self contained breathing apparatus should be worn. Remove to fresh air immediately.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight

# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Foreign Crude Oil

Skin contact	clothing such as a collar, tie, belt or waistband. Apply artificial respiration only if patient is not breathing but do not use mouth to mouth resuscitation. Get medical advice/attention if you feel unwell. IF ON SKIN (or hair): Remove contaminated clothing immediately and wash affected skin with plenty of water or soap and water. If irritation persists, get medical attention.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
Ingestion	IF SWALLOWED: rinse mouth. Do NOT induce vomiting. If unconscious, place in recovery position and get medical attention immediately. Wash out mouth with water and give small quantities of water to drink. Do not give anything by mouth to an unconscious person. Get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Do not wait for symptoms to appear. Immediately call a POISON CENTER/doctor.
<b>Most important symptoms and effects, both acute and delayed</b>	May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer. May cause damage to organs through prolonged or repeated exposure.
<b>Indication of any immediate medical attention and special treatment needed</b>	Treat symptomatically.
Notes to a physician:	IF SWALLOWED: Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs.

## SECTION 5: FIREFIGHTING MEASURES

### Extinguishing media

Suitable extinguishing media

Extinguish with sand or dry chemical. Foam, Carbon dioxide, Water fog or dry powder

Unsuitable extinguishing media

Do not use water jet. Direct water jet may spread the fire.

### Special hazards arising from the substance or mixture

Extremely flammable liquid and vapour. Will float and can be reignited on surface water. A mixture of solid and liquid particulates and gases including unidentified organic and inorganic compounds. May form explosive mixture with air. Prevent liquid entering sewers, basements and any watercourses. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. If sulphur compounds are present in appreciable amounts, combustion products may include also H<sub>2</sub>S and SO<sub>x</sub> (sulfur oxides) or sulfuric acid.

### Advice for firefighters

Fight fire with normal precautions from a reasonable distance. Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep containers cool by spraying with water if exposed to fire. Avoid release to the environment. Dike fire control water for later disposal.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Caution - spillages may be slippery. Ensure operatives are trained to minimise exposures. Ensure suitable personal protection during removal of spillages. Eliminate sources of ignition. Shut off leaks if without risk. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid all contact. Do not breathe vapour. Ensure adequate ventilation. Do not ingest. If swallowed then seek immediate medical assistance. Do not use sparking tools. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems.

### Methods and material for containment and cleaning up

Provided it is safe to do so, isolate the source of the leak. Use non-sparking equipment when picking up flammable spill. The vapour is heavier than air; beware of pits and confined spaces. Ensure that the equipment is adequately grounded. Allow small spillages to evaporate provided there is adequate ventilation. Wear flame-resistant antistatic protective clothing. Wear chemical protection suit and breathing apparatus.

# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Foreign Crude Oil

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling

Obtain special instructions before use. Keep away from sources of ignition - No smoking. Use only outdoors or in a well-ventilated area. Prevent vapour build up by providing adequate ventilation during and after use. May form explosive mixtures with air. Take action to prevent static discharges. Use non-sparking tools. All parts of the plant and equipment should be electrically bonded together and connected to earth. Electrical continuity should be checked at regular intervals. Antistatic clothing and footwear should be used. The vapour is heavier than air; beware of pits and confined spaces. Avoid all contact with substance. Do not ingest. If swallowed then seek immediate medical assistance. Do not breathe vapour. See Section: 8. Keep good industrial hygiene. Wash hands thoroughly after handling. Contaminated clothing should be thoroughly cleaned.

H2S Warning:

Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. These controls may include: Segregation of areas, Access only to authorised persons, Permit to work systems, Confined space working procedures, Area H2S alarms, Personal H2S alarms, Personal escape sets, H2S awareness training.

### Conditions for safe storage, including any incompatibilities

Light hydrocarbon vapours can build up in the headspace of containers. These can cause flammability / explosion hazards. Bund storage facilities to prevent soil and water pollution in the event of spillage. Keep only in original packaging. Keep containers properly sealed when not in use. Protect from sunlight. Containers of this material may be hazardous when empty since they retain product residue. Empty container may contain product residue which may result in flammable or explosive vapours inside the container.

Storage temperature  
Incompatible materials

Stable at ambient temperatures.  
Strong oxidising agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational exposure limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note
Petroleum	8002-05-9	-	350	-	1800	NIOSH
Hydrogen Sulfide	7783-06-4	-	-	10	15	NIOSH
		-	-	20	-	OSHA
		1	-	5	-	ACGIH
Benzene	71-43-2	0.1	0.42	1	3.2	NIOSH
		1	-	5	-	OSHA
		0.5	-	2.5	-	ACGIH
N-hexane	110-54-3	50	180	-	-	NIOSH
		50	1800	-	-	OSHA
		50	-	-	-	ACGIH
Toluene	108-88-3	100	375	150	560	NIOSH
		-	-	300	-	OSHA
		20	-	-	-	ACGIH

Note: OSHA PELs 1910.1000 TABLE Z-1/2/3 / NIOSH RELs / ACGIH TLVs

### Biological exposure indices

SUBSTANCE	CAS No.	Determinant	Biological Exposure Indices	Sampling Time	Note
Toluene	108-88-3	Toluene in blood	0.02 mg/l	Prior to last shift of workweek	-
		Toluene in urine	0.03 mg/l	End of shift	-
		o-Cresol in urine with hydrolysis	0.3 mg/g creatinine	End of shift	B

Source: ACGIH: American Conference of Governmental Industrial Hygienists - Biological Exposure Index (BEI) 2019

# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Foreign Crude Oil

Note:

B: Background

Nq: Nonquantitative

Ns: The determinant is nonspecific, since it is also observed after exposure to other chemicals.

## Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction if dusts, fumes or vapours are likely to be evolved. Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources. Guarantee that the eye flushing systems and safety showers are located close to the working place.

## Individual protection measures, such as personal protective equipment

Fuels are typically used, transferred and transported in closed systems. If exposure is likely (i.e. during sampling) the following advice may be appropriate. Keep good industrial hygiene. Always wash hands before smoking, eating and drinking. Do not eat, drink or smoke at the work place. Avoid all contact. Do not breathe vapour.

Protective clothing should be selected specifically for the working place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier.

Eye/ face protection



Use eye protection according to EN 166, designed to protect against liquid splashes.

Skin protection



**Hand protection:** Wear impervious gloves (recommended: EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Protective index 6, corresponding > 480 minutes of permeation time according to EN 374. Efficiency of at least 80%.  
Recommended: Nitrile rubber;  
Flouroelastomer (Minimum thickness – 0.5 – 0.65mm).

## Body protection: Wear anti-static clothing and shoes.

Small scale: Wear suitable coveralls to prevent exposure to the skin.  
Large scale: Chemical protection suit.

Respiratory protection



When the product is heated / In case of inadequate ventilation wear respiratory protection. The use of a high efficiency filter (recommended: EN143) is recommended. Filter type A1.

Closed system(s): Not normally required.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Dark brown liquid
Odour	Characteristic
Odour threshold	Not determined
pH	Not applicable
Melting point/freezing point	Not determined
Initial boiling point and boiling range	38 - 600°F
Flash point	38 - 180°F
Evaporation rate	Not determined
Flammability (solid, gas)	Not applicable - Liquid
Upper/lower flammability or explosive limits	Variable
Vapour pressure	0.5 - 7.5 psi
Vapour density	>1
Relative density	Not determined
Solubility(ies)	Insoluble

# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Foreign Crude Oil

Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature	Not determined
Decomposition temperature	Not determined
Viscosity	225 - 500 cSt

<b>Other information</b>	
Specific Gravity	0.86-0.98

## SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions. Reacts with - Strong oxidising agents
<b>Chemical stability</b>	Stable under normal conditions. Hazardous polymerisation will not occur. Product may release Hydrogen Sulphide.
<b>Possibility of hazardous reactions</b>	Extremely flammable liquid and vapour. May form explosive mixture with air. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. Product may release Hydrogen Sulphide.
<b>Conditions to avoid</b>	Elevated temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight.
<b>Incompatible materials</b>	Keep away from oxidising agents. Strong Acids and Alkalis.
<b>Hazardous decomposition products</b>	A mixture of solid and liquid particulates and gases including unidentified organic and inorganic compounds. Decomposes in a fire giving off toxic fumes: COx, H2S, SOx,

## SECTION 11: TOXICOLOGICAL INFORMATION

<b>Information on toxicological effects</b>	
<b>Acute toxicity - Ingestion</b>	Based upon the available data, the classification criteria are not met. Calculated acute toxicity estimate (ATE) >2,000 mg/kg.
<b>Acute toxicity - Inhalation</b>	Based upon the available data, the classification criteria are not met. Calculated acute toxicity estimate (ATE) > 5 mg/L (Vapour)
<b>Acute toxicity - Skin contact</b>	Based upon the available data, the classification criteria are not met. Calculated acute toxicity estimate (ATE) >2,000 mg/kg.
<b>Skin corrosion/irritation</b>	Based upon the available data, the classification criteria are not met.
<b>Serious eye damage/irritation</b>	Eye Irritation, Category 2A: Causes serious eye irritation.
<b>Respiratory or skin sensitisation</b>	Based upon the available data, the classification criteria are not met.
<b>Germ cell mutagenicity</b>	Based upon the available data, the classification criteria are not met.
<b>Carcinogenicity</b>	Carcinogen, Category 1B: May cause cancer. EU Harmonised Classification
<b>Reproductive toxicity</b>	Based upon the available data, the classification criteria are not met.
<b>STOT - single exposure</b>	Specific target organ toxicity — repeated exposure, Category 3 (Narcotic effects): May cause drowsiness or dizziness.
<b>STOT - repeated exposure</b>	Specific target organ toxicity — repeated exposure, Category 2: May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Aspiration hazard, Category 1: May be fatal if swallowed and enters airways. This product was conservatively classified under the basis of: high percentage inclusion of components with Aspiration hazard
<b>Information on likely routes of exposure</b>	
Inhalation	Possible – accidental exposure
Ingestion	Possible – accidental exposure
Skin contact	Possible – accidental exposure
Eye contact	Unlikely – accidental exposure
<b>Early onset symptoms related to exposure</b>	Causes serious eye irritation. May cause drowsiness or dizziness.
<b>Delayed health effects from exposure</b>	May cause cancer. May cause damage to organs through prolonged or repeated exposure.
<b>Exposure levels and health effects</b>	See Section: 8
<b>Interactive effects</b>	None known

# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Foreign Crude Oil

## Other information

OSHA Designated Carcinogen	Not listed
NIOSH Occupational Carcinogen List	Not listed
NTP Report on Carcinogens	Not listed
IARC Monographs	Listed

## SECTION 12: ECOLOGICAL INFORMATION

<b>Toxicity</b>	Hazardous to the aquatic environment, Chronic, Category 2: Toxic to aquatic life with long lasting effects.
<b>Persistence and degradability</b>	Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance
<b>Bioaccumulative potential</b>	Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance
<b>Mobility in soil</b>	Substance is complex UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance
<b>Other adverse effects</b>	None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

<b>Waste treatment methods</b>	Dispose of this material and its container as hazardous waste. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Disposal should be in accordance with local, state or national legislation. Containers of this material may be hazardous when empty since they retain product residue.
--------------------------------	--

## SECTION 14: TRANSPORT INFORMATION

	<b>Road/rail (ADR/RID)</b>	<b>Sea transport (IMDG)</b>	<b>Air (ICAO/IATA)</b>
<b>UN number</b>	UN1267	UN1267	UN1267
<b>UN proper shipping name</b>	PETROLEUM CRUDE OIL	PETROLEUM CRUDE OIL	PETROLEUM CRUDE OIL
<b>Transport hazard class(es)</b>	3	3	3
<b>Packing group</b>	I	I	I
<b>Environmental hazards</b>	Environmentally hazardous substance	Classified as a Marine Pollutant.	Environmentally hazardous substance
<b>Special precautions for user</b>	See Section: 2		
<b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable		

## SECTION 15: REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### US Federal Regulations

TSCA Chemical Data Reporting (CDR) Rule	Listed
NIOSH Occupational Carcinogen List	Not listed
EPCRA Section 313	Not listed
CWA 307- Toxic	Not listed
CERCLA - Hazardous Substances	Not listed
CWA Section 311 List of Hazardous Substances	Not listed

#### US State Regulations

Proposition 65 (California)	Not listed
Massachusetts, New Jersey, Pennsylvania, Rhode Island- State Right to Know Lists	Listed
New York -State Right to Know Lists	Listed
Minnesota - State Right to Know Lists	Listed
Massachusetts – Toxic Use reduction act	Listed

# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Foreign Crude Oil

Non-Regional  
IARC Monographs

Listed

## SECTION 16: OTHER INFORMATION

**The following sections contain revisions or new statements:** Updated substance / mixture classification. Updated version and date. New format has been issued, all sections have been updated to include new information. Review SDS with care.

**Version** 3.0  
**Revision Date** 14 April 2021  
**Date of First Issue** Not available. 2<sup>ND</sup> ISSUE RELEASED JUNE, 15 2015

This Safety Data Sheet was prepared in accordance with US Regulation OSHA HCS (29 CFR 1910.1200).

### References:

Existing Safety Data Sheet (SDS),  
EU Harmonised Classification and EU classification and labelling inventory for Petroleum (CAS. 8002-05-9).

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200	Classification procedure
Flammable Liquid, Category 1	Flash point
Aspiration hazard, Category 1	High percentage inclusion of components with aspiration hazard
Eye Irritation, Category 2	Threshold calculation
Specific target organ toxicity — repeated exposure, Category 3 (Narcotic effects)	Threshold calculation
Carcinogen, Category 1B	Threshold calculation
Specific target organ toxicity — repeated exposure, Category 2	Threshold calculation
Hazardous to the aquatic environment, Chronic, Category 2	Summation calculation

### LEGEND

ADR/RID	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road / RID: Regulations concerning the international railway transport of dangerous goods
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor (BCF)
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CWA	Clean Water Act
EC	European Community
ECHA	European Chemicals Agency
EPCRA	Emergency Planning and Community Right-to-Know Act
EN	European Standard
EU	European Union
IARC	International Agency for Research on Cancer
ICAO/IATA	International Civil Aviation Organization / International Air Transport Association
IMDG	IMDG: International Maritime Dangerous Goods
LC50	Lethal concentration at which 50% of the population is killed
LD50	Lethal dose at which 50% of the population is killed
LTEL	Long term exposure limit
OECD	Organisation for Economic Cooperation and Development
OSHA	The Occupational Safety & Health Administration
STEL	Short term exposure limit
TSCA	Toxic Substance Control Act
TWA	Time Weighted Average
UN	United Nations
UVCB	Unknown or Variable Composition

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.



# SAFETY DATA SHEET



Revision: 3.0 Date: 14 April 2021

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

**Foreign Crude Oil**

## Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. VITOL INC gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. VITOL INC accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.